



STAINLESS STEEL PIPE STRAPPING
PLAN VIEW

MATCH EXISTING GRADE MORTAR -24" CLEAR OPENING RING AND COVER - SEE NOTES 4" MIN TO 12" MAX PRECAST CONCRETE RINGS, CAST WITH GROOVE SO THAT SAFETY STEP 18" MAX CAN BE FIELD INSTALLED PRECAST ECCENTRIC CONE 54" TO 24" OR REDUCING SLAB ON SHALLOW MANHOLE CUT TEE 22.5° 54" **NEW PVC PIPE** SELECT BACKFILL OR NATIVE MATERIAL .5D-SUBJECT TO ENGINEERS **APPROVAL** SAFETY STEP AND LADDER. SEE DETAIL CK-S.14 PRECAST CONCRETE SECTION 1FT, 2FT, 3FT, OR 4FT AS KOR-N-SEAL BOOT NECESSARY. ELBOW CLOCKED 45° TO MAIN CHANNEL IF ENTERING FROM SIDE - SEE PLAN VIEW. Control of the second FORM CHANNEL WITH CLASS "E" CONCRETE AS REQUIRED BEDDING MATERIAL - 6" MIN. FOUNDATION MATERIAL

NOTES:

- 1. USE ONLY WHEN APPROVED BY PUBLIC WORKS.
- 2. NO EXTERNAL DROPS ALLOWED.

CITY OF KIRKLAND

PLAN NO. CK-S.12



SANITARY SEWER INTERNAL DROP CONNECTON